

## Green Tinted Lenses

<b>Part Number</b>	88VXOLG
<b>Material</b>	Acetate
<b>Thickness</b>	0.042"
<b>Packaging</b>	25 lenses per pack
<b>Color</b>	14 +/- 4 percent visible light transmittance
<b>ANSI/ISEA</b>	Z87.1-2010 Face Protection (When used as a part of the complete assembly)

## Smoke Tinted Lenses

<b>Part Number</b>	88VXOLT
<b>Material</b>	Tritan™
<b>Thickness</b>	0.030"
<b>Color</b>	Approximately 10 percent visible light transmittance
<b>Packaging</b>	25 lenses per pack
<b>ANSI/ISEA</b>	Z87.1-2010 Face Protection (When used as a part of the complete assembly)



## Installation and Use

The 88VXOLG and 88VXOLT are for use with the 88VX Series Respirator. These outer lenses are installed into the door assembly by sliding the lenses underneath the retaining clips. The 88VXOLG is typically installed with two clear .015" outer lenses and the 88VXOLT is typically installed with three clear .015" outer lenses to prolong the life of the tinted lenses.

**Americas:**  
**Bullard**  
1898 Safety Way  
Cynthiana, KY 41031-9303 • USA  
Toll-free within USA: 877-BULLARD (285-5273)  
Tel: +1-859-234-6616  
Fax: +1-859-234-8987

**Europe:**  
**Bullard GmbH**  
Lilienthalstrasse 12  
53424 Remagen • Germany  
Tel: +49-2642 999980  
Fax: +49-2642 9999829

**Asia-Pacific:**  
**Bullard Asia Pacific Pte. Ltd.**  
LHK Building  
701, Sims Drive, #04-03  
Singapore 387383  
Tel: +65-6745-0556  
Fax: +65-6745-5176



©2013 Bullard. All rights reserved.  
Tritan is a trademark of Eastman Chemical Company.